

FSM4662

46-inch Industrial LCD Monitor

Features

- 46" TFT LCD Monitor with Resolution up to 1920 x 1080
- IP65 Waterproof Front Bezel, Rugged Housing
- 700/1500nits High Brightness for Sunlight Readable (Optional)
- Wide Temperature Support -30°~+60°C (Optional)
- IR Touch / P-CAP Touch (Optional)



SPECIFICATION

Display	Size/Panel Type	46" TFT LCD Panel
	Resolution	1920 x 1080
	Brightness (cd/m ²)	500cd/m ² (Optional: 700/1500cd/m ²)
	Contrast Ratio	4000:1
	Response Time	6.5ms
	Backlight	LED backlight unit
	Colors	16.7M Colors
	Viewing Angle (H/V)	178°/178°
Touch Screen	Touch Screen Type	IR Touch / P-CAP Touch (Optional)
	Surface Hardness	7H
Environment	Operating Temperature	0°~50°C
	Storage Temperature	-20°C~+60°C
	Humidity	5%~95% RH(Non-Condensing)
	Waterproof Rating	IP65 Waterproof Front Bazel
System	OSD	Menu, Auto, On/Off, Up, Down
	I/O Interface	DVI x 1, VGA x 1, HDMI x 1, Power in x 1
	Power Input	AC100~240V input
	Power Consumption	110W
	Certification	FCC/CE/RoHS Compliance
	Mounting	VESA 400 x 400mm
	Dimension/Weight	1110mm (W) x 665mm (H) x 80mm (D)/42kgs

Specifications subject to change without notice



ORDERING CODE

FSM4662-XXXX

- PCT = P-CAP Touch Screen
- IR = IR Touch Screen
- HB700 = 700nits High Brightness
- HB1500 = 1500nits High Brightness
- W = Wide Temperature, -30°~+60°C
- LS = Light Sensor, Auto Dimming

ACCESSORIES

- VGA Cable x 1 (1.8M)
- AC Power Cord x 1 (1.8M)



Unit:mm